



THE LABORATORY
AT THE BIRMINGHAM
ASSAY OFFICE

P.O. BOX 151 NEWHALL STREET
BIRMINGHAM B3 1SB ENGLAND

TELEPHONE: +44 (0)121 236 6951
FACSIMILE: +44 (0)121 236 3228

www.theassayoffice.co.uk
testing@theassayoffice.co.uk

Bijoux Bioflex

Full Nickel Release Test Report

Ref: 71967	Date: 22 September 2009
Page: 1 of 1	Date work received: 14 September 2009

Method:	Sample(s) of the product(s) listed below have been tested according to procedures based on BS EN 12472:2005 and BS EN 1811:1999, as required by The Dangerous Substances and Preparations (Nickel) (Safety) Regulations 2005 No. 2001. Wherever practical, product(s) have been disassembled into their component parts and the nickel release determined for each component. No parts of the product have been 'masked off' during the test, unless specifically instructed by the Customer.
Results:	Results relate only to the specific product(s) tested.
Units:	Nickel released in micrograms per square centimetre per week.
C or N/C	C= compliant with section 3(1)(a) of the Dangerous Substances and Preparations (Nickel) (Safety) Regulations 2005 for a post assembly, section 3(1)(b) for an un-plated product, or section 3(1)(c) for a plated product.

Customer Reference	Description	Adjusted Nickel Release	Compliant (C) or Non-Compliant (N/C)
BIOFLEX	Sample	Less than 0.1	C

NOTES: I). Prior to the release test, where practical products were disassembled and any newly exposed surfaces coated with a masking agent.

B. Perry BSc, PhD
Technician

M. Tart
Senior Technician

KM 15.21

Note: The information contained in this report is given in good faith on the basis of samples and information received. The Assay Office does not take responsibility for the Customer's interpretation of the report nor any consequence arising from this. This test report shall not be reproduced except in full, without written approval of the Assay Office. Our standard conditions and tolerances apply. Opinions and interpretations are outside the scope of accreditation.



FS 24058



0667